## **Summary of Overall Standards of Performance:-Q1 FY25-26**

Sr No	Service Area	Overall Standards of Performance	Total Cases Received/ Reported (A)	Complaints Attended (B)		Standard of
				Within Specified Time	Beyond specified time	Performance achieved (C )%
		Dayway Core	ala Fallana			
1	Power Supply Failure					
(i)	Continuous power failure affecting individual consumer and group of consumer upto 100 connected at Low voltage supply, excluding the failure where distribution transformer requires replacement.	- At least 95% calls received should be rectified within prescribed time limits	125511	124709	649	99.36%
(ii)	Continuous power failure affecting more than 100 consumers connected at Low voltage supply excluding the failure where distribution transformer requires replacement.		1044	1034	9	99.04%
(iii)	Continuous power supply failure requiring replacement of distribution transformer.		1	1	0	100.00%
(iv)	Continuous power failure affecting consumers connected through High Voltage Distribution System (HVDS) and not covered under (i) & (ii) above	At least 95% calls received should be rectified within prescribed time limits	104	103	1	99.04%
(v)	Continuous scheduled power outages	At least 95% of cases resolved within time limit	933	933	0	100.00%
(vi)	Replacement of burnt meter or stolen Meter		4166	4165	0	99.98%
		Period of Schedul	ed Outage			
2	Maximum duration in a single stretch	At least 95% of cases resolved within time limit	923	923	0	100.00%
	Restoration of supply by 6:00 PM		923	923	0	100.00%
3	Faults in street light maintained by the Licensee	At least 90% cases should be complied within prescribed time limits	5188	5173	15	99.71%
	Reliability Indices					
4	SAIFI	To be laid down by the Commission based on SAIDI the targets proposed by the	0.33			
	SAIDI		0.36			
	CAIDI	Licensees.	1.09			
5	Frequency variation	To maintain supply frequency within range as per IEGC.				
6	Voltage imbalance	Maximum of 3% at point of commencement of supply		No. of Bills Served	Bills with Mistakes	
7	Percentage billing mistakes	Shall not exceed 0.2%		6328255	240	0.004%